


8038 Sealing Crystals 8.00X3.80X2.54mm



Applications

- RTC.

Features

- Dimensions: :8.00 x 3.80 x 2.54mm.
- Standard Frequency: 32.768KHz
- Reflow is possible.
- Contains Pb in sealing glass exempted by ROHS directive.

Electrical Specifications

Item	Symbol	Specifications
Nominal Frequency (额定频率范围)	f_nom	32.768KHz
Load Capacitance (负载电容)	CL	7pF, 9pF, 12.5pF, or specify±
Frequency Tolerance (频率偏差) (at 25°C)	f_tol	10ppm, ±20ppm, or specify
Parabolic Coefficient (频率温度系数)	B	(- 0.036 ± 0.006) * 10 ⁻⁶ / °C ²
Operating Temperature (工作温度)	T_use	-40~+85°C
Storage Temperature (储存温度)	T_stg	-55~+125°C
Shunt Capacitance (静态电容)	C0	2.0pF Max.
Motional Capacitance (动态电容)	C1	3.0fF
Level of Drive (激励电平)	DL	1.0μW Max
Aging (老化) (at 25°C)	f_age	±5ppm/year Max.

Equivalent Series Resistance(等效串联电阻ESR)

8038
50K Ω Max.

Dimensions and Recommendes land pattern(外观尺寸及推荐焊盘)

Dimensions (Unit: mm)	
	<p>(TOP VIEW)</p>